

AU / NZ

Edition

10/2022

DIMENSIONS

		PULSE CLICK+
Collection		
Width		209 mm
Length		1494 mm
Number of panels per pack		6 Panels
Weight per box		15,5 kg
m ² per pack		1,873 m ²
Density		1350 ± 50 Kg/m ³
Total thickness	ISO24346	6 (= 5+1) mm
Finishing	Advanced PU -Top coating with scratch & Stain Guard technologie	
Tongue and groove	Uniclic connection	

FACTORY WARRANTY

Usage class	EN ISO 10874 classification	Class 33
Product norm	EN 16511:2014 + A1:2019	
CE	EN 14041:2004 / AC:2006	DOP: QRHC 0501
Warranty	Residential use Commercial use	See warranty conditions See warranty conditions
		25 years 5 years - on request up to 15 years

GENERAL DATA

	METHOD	PARAMETERS	NORM REQUIREMENTS	QUICK-STEP VALUES
Wear resistance	EN 16511:2014 + A1:2019		OK	OK
Impact resistance	EN13329 - Annex F		≥ 1600 mm	≥ 1600 mm
Scratch resistance	EN16094		≤ MSR-A2 ≤ MSR-B2	≤ MSR-A1 ≤ MSR-B2
Castor chairs	EN 425	25000 cycles	No delamination, no disturbance	OK
Displacement of furniture feet	EN 424	Foot 0,1 mm / 32 kg		No visible damage
Residual indentation	EN ISO 24343-1		≤ 0,2mm	OK
Resistance against staining	EN 438-2	Acetone - Coffee - NaOH - H2O2 - Shoe Polish		Grade 5 No change
Swelling	ISO 24336		≤ 18%	no swelling
Locking strength	ISO 24334	Fmax long side Fmax short side	> 1,0 kN/m > 1,5 kN/m	> 2 kN/m > 3 kN/m
Dimensional stability	ISO 23999	6 hrs at 60°C Cupping	≤ 0,25% < 1mm	≤ 0,15% < 1mm
Fire classification	AS/ISO 9239.1 - 2003			9,4 Kw/m ² 111%/min
UV resistance	ISO 105 B02	Blue reference	Class >6	Class 8
Slip resistance	AS 4586:2013			P4
Thermal resistance	EN 12667	Rigid preattached underlay		0,044 m ² KW
Floor heating	Appropriate for all standard heating systems IN cement flooring, NOT appropriate for heating films and alternatives. Max contact temp ≤ 27°C. See separate installation instructions.			

ENVIRONMENT & CERTIFICATES

AFFSET		A+
Formaldehyde emission	EN 14041:2004/AC:2006	E1
TVOC 28 days	ISO16000 part 9-6	≤ 20µg/m ³
Content	Heavy metals+ lead/cadmium	NOT present
Dangerous substances	Carcinogenic, mutagenic or reprotoxic substances class 1A and 1B (candidate list)	NOT present
REACH	Regulation (EC) No 1907/2006	Compliant
Plasticizer	Ortho-phthalate free plasticizer	
Recycled content	Only INTERNAL recycled material used	

